

## CA-MI NEW ASKIR SUCTION UNIT 30 POLYCARBONATE JAR 1L



Ref. BCASPI12



29/08/2024 14:44:32 - For information purposes only, can be subject to change

GSH | 30 rue Jean de Guiramand  
13290 Aix-en-Provence | France

[www.gsh-med.fr](http://www.gsh-med.fr)

+33(0)4 42 90 31 31

[info@gsh-med.fr](mailto:info@gsh-med.fr)

## CA-MI NEW ASKIR SUCTION UNIT 30 POLYCARBONATE JAR 1L



Ref. BCASPI12

Fixed electric surgical Suction Unit, intended to drain body fluids and to perform oral, nasal and tracheal aspiration in adults and children.

### Description

Ca-mi New Askir 30 Suction Unit, autoclavable polycarbonate jar, 1000 ml

Fixed electric surgical Suction Unit, intended to drain body fluids and to perform oral, nasal and tracheal aspiration in adults and children.

Suitable for tracheostomy patients and is ideal for minor surgical applications as well as postoperative home treatments.

Main applications: Endoscopy, Gastroenterology, General surgery, Home care, Obstetrics, Room, Veterinary Med.

-

The main system is equipped with a pressure gauge (bar & kPa) and a vacuum regulator

-

Optional roller foot-

Supplied accessories: Fluid collection jar with an anti-reflux valve with different options / Silicone hoses (autoclavable) 6 x 10mm and conical connectors  $\varnothing$  8-9-10 mm / Antibacterial & hydrophobic filter (single patient) / CH20 cannula / Power cord with Schuko plug

- Engine: Oil-free piston pump requiring no maintenance

-

Power supply: 230V-50Hz - other configurations available on request

-

Maximum vacuum (adjustable): 0.80 Bar -80 kPa -600 mmHg

-

Max free air flow: 40 l/min

-

Noise level: 60.5 dBA


- Uninterrupted operating cycle

- Weight: 3.6 kg / Dimensions: 35 x 21 x 18 cm

 **atures** 2024 14:44:32 - For information purposes only, can be subject to change

GSH | 30 rue Jean de Guiramand  
13290 Aix-en-Provence | France

 [www.gsh-med.fr](http://www.gsh-med.fr)

 +33(0)4 42 90 31 31

 [info@gsh-med.fr](mailto:info@gsh-med.fr)

Packed unit / Length (cm)	nc	Packed unit / Weight	3.8
Bare Unit / Weight (kg)	3.6		
SPECIFIC STORAGE CONDITIONS			
Minimum temperature	-20	Max temperature	45
Minimum humidity	1	Maximum humidity	85
OTHER FEATURES			