

LUXASCOPE AURIS LED 2.5 V - LUXAMED

LUXAMED®

Ref. A1.416.214



14/11/2024 21:48:31 - For information purposes only, can be subject to change

GSH | 30 rue Jean de Guiramand
13290 Aix-en-Provence | France

www.gsh-med.fr

+33(0)4 42 90 31 31

info@gsh-med.fr

LUXASCOPE AURIS LED 2.5 V - LUXAMED

LUXAMED®

Ref. A1.416.214

Innovative otoscope in pocket size

Description

Illumination: LED-Ring with 6 LEDs (concentric),

no fibre optic, field of vision is not restricted

- Maintenance-free, because no lamp replacement necessary
- Can be dimmed
- Automatic switchoff after 3 minutes
- Life expectancy of LEDs: approx. 100.000 hours

by constant current drive

- Intensity of illumination: approx. 10.000 Lux
- Colour temperature: approx. 4.200 K
- Optimized design of head
- Pivoting 3-fold magnifying glass with locking function
- Insufflation port for pneumatic test
- Two-component handle (aluminium / fibre-glass reinforced),

also combinable with LuxaScope LED Dermatoscope- and

Ophthalmoscope head

- Electronic ON/OFF push-button switch
- Power supply: 2x AAA Alkaline batteries, inclusive
- Incl. 20 disposable ear funnels, grey,

each 10 x 2.5 mm and 10 x 4.0 mm

 14/11/2024 21:48:31 - For information purposes only, can be subject to change

GSH | 30 rue Jean de Guiramand
13290 Aix-en-Provence | France

 www.gsh-med.fr

 +33(0)4 42 90 31 31

 info@gsh-med.fr

LUXASCOPE AURIS LED 2.5 V - LUXAMED

LUXAMED®

Ref. A1.416.214

Features

CE Marking	CE	Medical device	Class I
Bar code	04260381960027	HS Code	90189084
Warranty (months)	24	Country	Germany
DIMENSIONS AND WEIGHT			
Packed unit / Width (cm)	nc	Packed unit / Height (cm)	nc
Packed unit / Length (cm)	nc	Packed unit / Weight	nc
SPECIFIC STORAGE CONDITIONS			
Minimum temperature	5	Max temperature	40
Minimum humidity	10	Maximum humidity	90
OTHER FEATURES			
Colors	Blue		

 14/11/2024 21:48:31 - For information purposes only, can be subject to change

GSH | 30 rue Jean de Guiramand
13290 Aix-en-Provence | France

 www.gsh-med.fr

 +33(0)4 42 90 31 31

 info@gsh-med.fr